


◆ MODEL 型式

VPK-12U



◆ PERFORMANCE (Cartridge Only) 特性曲線



◆ SPECIFICATIONS 規格

Model Number 型式號碼	Maximum Pressure 最大壓力 bar	Cracking Pressure 開啟壓力 bar	Pilot Ratio 引導比例	Maximum Flow 最大流量 Lpm	Weight 重量 Kg
VPK-12U	350 (5076 psi)	2 (29 psi)	4 : 1	120 (31.70 gpm)	0.26 (0.57 lbs)
Fluid Type 液體型式			ISO VG 32,46,68		
Viscosity 黏性 cSt			10-400 (59-1854SSU)		
Operating Temperature 操作溫度 °C			-15~70 (-5~158°F)		
Contamination Level 污染標準			ISO4406. 21/19/16 NAS1638,10		

◆ HOW TO ORDER 編號說明

1	2	3
VPK	12U	*

1 VALVE SERIES 系列名稱

VPK=CARTRIDGE PILOT OPERATED CHECK VALVES

插入式引導止逆閥


2 SUBPLATE MOUNTING SIZE 轉印口徑

Size : 12U


Cavity 孔口:A12336

3 DESIGN NO 設計編號

◆ CONTROL PORT(S) 動作形式



◆ DIMENSIONS 外型尺寸圖



A12336

